

Model DESR-PWB



Brand Powered by >>>

Sensotech



WIRING SCHEMATIC	
COLOUR CODE	CONNECTION
RED	EXCITATION (+)
BLACK	EXCITATION (-)
GREEN	OUTPUT (+)
WHITE	OUTPUT (-)
SHIELD	GROUND

CAPACITY (T)	CAPACITY RANGE 20 TF				
	A	B	C	D	G
DESR 20	240	92	92	300	35



Performance Data

Capacity Range (in kgf)	
Capacity Range (in Tf)	20
Nominal Sensitivity (mV/V)	2±0.25%
Zero Signal Tolerance	0±2%
Input Resistance	700±5Ω
Output Resistance	700±3Ω
Recommended Excitation Voltage	10 VDC
Maximum Excitation Voltage	25 VDC
Linearity Deviation (as % of Full Scale)	<±0.020
Repeatability (as % of Full Scale)	<±0.020
Hysteresis (as % of Full Scale)	<±0.020
Creep (as % of Full Scale) in 30 min	<±0.020
Effect of Temperature on Zero( % / o C)	±0.002
Effect of Temp. on Span ( % / o C of Load)	±0.001
Compensated Temperature Range	-10 to + 40°C
Operating Temperature Range	-20 to 70°C
Combined Error (as % of Full Scale)	<±0.03 max
Isolation Resistance (@ 50 VDC)	>1000 M Ω
Max. Limit Force (as % of Full Scale)	150
Breaking Force (as % of Full Scale)	300
Lateral Load Limit (as % of Full Scale)	500.1
Protection Class	IP 68
Material of Construction	High Nickel Alloy Steel

Features

- In-built Lightning Protection
- Low Deflection & Creep
- Allows High Permissible Dynamic Load
- Insensitive to Eccentric Load

Optional

Explosion Proof Version Suitable for Group I,IIA, IIB, IIC & meet Temperature Class T4

Application

Portable Weighbridge, Coil car Weighing, onboard Weighing Scale

Sensotech: No. 2/675, "The Palms" 1st Cross Street, Ranga Reddy Garden, Neelankarai, Chennai - 600 041.



+(91)-(44)-2449 4305

+(91)-(44)-6050 4460



+(91)-73057 16667 +(91)-98848 69600

+(91)-93805 60667 +(91)-93424 78988



sales@sensomaticloadcell.in  
sensotechindia@gmail.com  
sensotech@vsnl.net



www.sensomaticloadcell.in  
www.sensomaticloadcell.com  
www.sensomaticloadcell.net